

**CONDITIONS OF TRANSPORT, STORAGE AND USE OF THE PRODUCTS**

**Plast-Farb Sp. z o.o. ul Skłodowskiej-Curie 87A  
87-100 Toruń, tel. +48 56 644 85 40  
e-mail: [plastfarb@plast-farb.com](mailto:plastfarb@plast-farb.com), [www.plast-farb.com](http://www.plast-farb.com)**

Product	BAGS	MAILING BAGS (COURIER BAGS)	SECURITY PACKAGING - EQUIPPED WITH SAFETY TAPE	CARRY BAGS AND MAILING BAGS (COURIER BAGS)
<b>applications</b>	Commercially used products that enable placement on the product of any print that is the source of the company's identification and advertising	These products are aimed at companies dealing in logistics, forwarding and e-commerce. Mailing bags are used to send and store shipments resistant to mechanical damage. Items placed in them should not have sharp edges. The sealed envelope protects the shipment in the temperature range -15°C to +40°C, i.e. in these conditions the envelope will not open under the influence of the force exerted by its contents. The foil packaging protects the contents against moisture, The opaque layer of foil ensures discretion and the possibility of placing any print on the product can be a source of identification and advertising of the company.	These products are intended for storing and transporting money and other valuables. This type of packaging is fully protected against interference by third parties.	Advertising bags - products used in trade. Courier bags - these products are aimed at companies dealing in logistics, forwarding and e-commerce. Mailing bags are used to send and store shipments resistant to mechanical damage. Items placed in them should not have sharp edges. The sealed envelope protects the shipment in the temperature range -15°C to +40°C, i.e. in these conditions the envelope will not open under the influence of the force exerted by its contents. The foil packaging protects the contents against moisture, The opaque layer of foil ensures discretion and the possibility of placing any print on the product can be a source of identification and advertising of the company.
<b>transport</b>	- temperature: -15°C to +40°C - humidity: up to 80% (exception BIO up to 50%)		- temperature: -5°C to +30°C - humidity: up to 80% - temperature above +40°C or below -5°C lasting longer than 3h may induce thermal protection used in the security tape and cause its irreversible color change.	- temperature: -15°C to +40°C - humidity: up to 80% (exception BIO up to 50%)
Truck with tarpaulin to avoid exposure to the negative effects of weather conditions, mainly direct sunlight and rain. Loading units should be clean and free from foreign odors. The cargo should be secured against displacement, dirt and damage.				
<b>storage</b>	- temperature: +5°C up to +30°C - humidity: up to 80% (exception BIO up to 50%) The temperature above +40°C or below -5°C for more than 3h may induce the thermal protection used in the security tape and cause its irreversible color change. Do not store packages near heat sources, do not store near volatile organic solvents and inorganic solvents. The packaging should be protected against direct effects of weather conditions, especially sunlight and rain, the room should be clean, free from foreign smells and not damp.			
<b>terms of use</b>	- the bags have a handle that makes it easier to carry the goods inside - the handle can be without or with additional reinforcement	- closing the product should be placed at a temperature not lower than +15°C and in a dry atmosphere - in order to ensure optimal physicochemical properties, products transported or stored at low temperatures (below +5°C) should be conditioned at room temperature for 24 hours before use - the application of the adhesive layer achieves optimum adhesion after 10 minutes from sticking and protects the parcel during storage and transport under the conditions specified above		
<b>way of usage</b>		- after placing the contents in the mailing bag, smoothly remove the corner that protects the adhesive layer - then bring the adhesive layer closer to the opposite slot, press firmly and carefully with your fingers along its entire length - an unauthorized attempt to open the envelope will result in the formation of visible and permanent traces in the form of a stretched, deformed foil	- after placing the contents in the security bag, remove the corner in a smooth manner ("without jerking") - then bring the security tape with glue close to the opposite inlet, press firmly and carefully with your fingers along its entire length - security tape reaches full functionality after approx. 10 minutes from sticking - the security features used in the security tape guarantee that <b>an attempt to open it will result in visible and permanent traces</b>	- after placing the contents in the security bag, remove the corner in a smooth manner ("without jerking") - then bring the security tape with glue close to the opposite inlet, press firmly and carefully with your fingers along its entire length - an unauthorized attempt to open the envelope will result in the formation of visible and permanent traces in the form of a stretched, deformed foil
<b>type of film:</b>	LDPE, HDPE or MDPE high-strength; transparent or colored, with or without reggranulate (including 80% PCR), BIO - based on PLA			l'm green - polyethylene based on bio-thermoplastic resin derived from sugar cane
<b>warranty</b>	THE RECIPIENT SHOULD MAKE THE QUANTITATIVE AND QUALITATIVE CHECKS WITHIN THE PERIOD NOT EXCEEDING 7 DAYS FROM RECEIVING THE DELIVERY THE MANUFACTURER PROVIDES WARRANTY FROM THE DATE OF MANUFACTURE, PROVIDED IN APPROPRIATE CONDITIONS OF TRANSPORT, STORAGE AND USE FOR 12 MONTH (EXCEPTION - BIO 6 MONTH).			